

CHARGING MODES (VARIES BY DEVICE)

1 Standard Charging Mode (up to 15W)

Voltage: 9V DC (5V for very low power states)

Current: up to ~1.67A at 9V

Power: ~15W max output to the device

2 Fast Charging Mode (15W, certified Qi2)

Qi2 mandates USB-C with USB Power Delivery (PD) negotiation.

Voltage Profiles Negotiated via PD:

- 5V (standby/low load)

- 9V (normal operation for up to 15W)

3 Power Source Requirements

To reliably support Qi2 at full 15W, your power adapter should be PD-compliant and rated for at least:

- 9V @ 2A (18W minimum PD profile)

- A 20W PD adapter is recommended to allow headroom and maintain full speed even with inefficiency

WARRANTY INFORMATION

Safety Guidelines:

Stop the vehicle in a safe location or have a passenger use the system.

Safely operate the vehicle, obey all laws and regulations, and use good judgment at all times. Note: User assumes sole responsibility for and all risk in using this system.

General Guidelines:

Install the device in a non-obstructive, safe location within the vehicle cab. Avoid obstructing the following: Vehicle operation, Visibility through windows, Safe entry or exit, Safety devices such as air bags. Firmly secure the device to stay in place despite vibrations, shocks bumps, or vehicle accidents. Do not use this system or any computer system while operating a motor vehicle. Mob Armor is not responsible or liable for personal and or property damage.

What does your 100% Satisfaction Guarantee mean?

Our 100% Satisfaction Guarantee means we guarantee you will be satisfied with your Mob Armor Product, or we will refund your money. If you are unsatisfied with your product at any time within 30 days of your purchase, you can return it to us for a full refund, no questions asked. You pay shipping back to us. We do not refund any shipping cost.

What warranty does Mob Armor offer?

The Mob Armor Warranty covers all defects in workmanship or materials of our products for up to three years from time of purchase. This warranty applies only to the original purchaser at retail and may not be transferred. This warranty only covers defects arising under normal usage and does not cover any malfunction, damage or failure due to accident, misuse, abuse, neglect, alteration, modification or repair by other than an authorized service center for Mob Armor products. Scratching of the powder-coated surface, anodizing or plastic constitutes normal wear and is not covered under warranty. For complete warranty information please visit mobarmor.com/warranty

IMPORTANT!

DO NOT RETURN PRODUCT TO RETAILER!

IF YOU NEED WARRANTY SERVICE OR REPLACEMENT PARTS, PLEASE REACH OUT TO US DIRECTLY!

(805) 214-1815

OR VISIT MOBARMOR.COM/WARRANTY TO SUBMIT A CLAIM

 **MOB ARMOR.**



FLEXCHARGE 2
PRODUCT INSTRUCTIONS & WARRANTY

FLEX CHARGE 2

INCLUDED IN THE BOX:

- FLEX Charge 2.0 Wireless Charger with Integrated USB-C Cable

INITIAL OPERATION

- 1 Plug mount in to USB-C port (ideally PD compliant) with at least 15W output.
- 2 Place phone on wireless charger to verify charging is successful before attaching charger to a magnetic phone mount.

Need support? Call **(805) 214-1815** or visit mobarmor.com/support to chat with us

CHARGING YOUR DEVICES

- 1 **MagSafe® compatible phones (iPhone® 12 and newer)** - The charger will attach magnetically and initiate charging automatically.
- 2 **Non-MagSafe® compatible phones (most Android™ phones, iPhone 11® and earlier)** - If your phone has Qi / Qi2 wireless charging capability, it will charge but it will **NOT** magnetically mount. Use our **FLEX Plate+** (sold separately), or a MagSafe® compatible phone case designed for your phone for magnetic mounting.
- 3 **Headphones and other Qi / Qi2 wireless charging devices** - Place your device on the center of the wireless charger. Your device should have a status light to indicate charging.

+ Visit MobArmor.com/ReplacementParts to purchase FLEX Plate for additional magnetic mounting strength on all phones

ATTACHING TO A PHONE MOUNT

- 1 Ensure phone mounting location will allow USB-C cord to reach charging port. Plug in to charging port.
- 2 Attach wireless charger to phone mount before placing on dashboard / mounting location. Ensure charger has center alignment with mount.
- 3 Follow phone mount installation instructions before placing mount in desired location. Your charger is now ready for use!



COMPATIBLE MOB ARMOR MOUNTS

- MobNetic Maxx
- MobNetic ICON
- MobNetic Stixx
- MobNetic CLAW
- MobNetic GO
- MobNetic SLIM
- All future MobNetic mounts



Compatible with **Standard Magnet** and **Non-Charging MagSafe®** mounts