

WARRANTY INFORMATION

Safety Guidelines:

Stop the vehicle in a safe location or have a passenger use the system. Safely operate the vehicle, obey all laws and regulations, and use good judgment at all times. Note: User assumes sole responsibility for and all risk in using this system.

General Guidelines:

Install the device in a non-obstructive, safe location within the vehicle cab. Avoid obstructing the following: Vehicle operation, Visibility through windows, Safe entry or exit, Safety devices such as air bags. Firmly secure the device to stay in place despite vibrations, shocks bumps, or vehicle accidents. Do not use this system or any computer system while operating a motor vehicle. Mob Armor is not responsible or liable for personal and or property damage.

What does your 100% Satisfaction Guarantee mean?

Our 100% Satisfaction Guarantee means we guarantee you will be satisfied with your Mob Armor Product, or we will refund your money. If you are unsatisfied with your product at any time within 30 days of your purchase, you can return it to us for a full refund, no questions asked. You pay shipping back to us. We do not refund any shipping cost.

What warranty does Mob Armor offer?

The Mob Armor Warranty covers all defects in workmanship or materials of our products for up to three years. This warranty applies only to the original purchaser at retail and may not be transferred. This warranty only covers defects arising under normal usage and does not cover any malfunction, damage or failure due to accident, misuse, abuse, neglect, alteration, modification or repair by other than an authorized service center for Mob Armor products. Scratching of the powder-coated surface, anodizing or plastic constitutes normal wear and is not covered under warranty. For complete warranty information please visit mobarmor.com/warranty

IMPORTANT!

DO NOT RETURN PRODUCT TO RETAILER!

IF YOU NEED WARRANTY SERVICE OR REPLACEMENT PARTS, PLEASE REACH OUT TO US DIRECTLY!

(805) 214-1815

OR VISIT MOBARMOR.COM/WARRANTY
TO SUBMIT A CLAIM

NOTES

THANK YOU FOR SUPPORTING
MOB ARMOR.

Let the world know how much you love Mob Armor gear by leaving a review at MobArmor.com, or wherever you placed your order!



THICK MOB DISC
PRODUCT INSTRUCTIONS & WARRANTY

THICK MOB DISC

The Thick Mob Disc creates a thicker, stronger mounting point on dashboards, walls, panels, and other surfaces where extra holding strength is needed for your Mob Armor magnetic phone mount.

INCLUDED IN THE BOX

- 1 Thick Mob Disc
- 1 #6 x 1/2" self-drilling flat head screw
- 1 #8 x 1" self-drilling flat head screw
- 1 8-32 x 5/8" flat head machine screw
- 1 oversized backing washer
- 1 8-32 serrated flange nut



PN 10138 REV 52926

BEFORE YOU START

- Choose a flat, solid mounting location.
- Verify there are no wires, airbags, electronics, or hidden components behind the surface before drilling.
- Use the through-bolt method whenever the surface is thin, flexible, or weak.
- Do not install in any location that could create a safety issue or damage the vehicle or mounting surface.

KEEP IN MIND...

- For the strongest hold on thinner panels or dashboards, use the through-bolt method (Mounting Option #2) with the included washer and nut.
- Professional installation is recommended if you are unsure about drilling into a dashboard or interior panel.
- Installer is responsible for verifying clearance behind the surface before drilling.
- Periodically inspect the hardware and retighten if necessary.

MOUNTING OPTION #1 - DIRECT SCREW MOUNT

Best for: thick plastic, wood, composite panels, or other solid surfaces.

HARDWARE USED IN THIS PHASE:

- Thick Disc
- One self-drilling screw: use either the #6 x 1/2" screw or the #8 x 1" screw based on your material thickness and application

INSTRUCTIONS

- 1 Place the Thick Mob Disc in the desired location and mark the center hole.
- 2 Drill a pilot hole if needed.
- 3 Position the disc with the countersunk hole facing outward.
- 4 Insert one self-drilling screw through the center hole of the disc.
- 5 Tighten until the screw head sits flush and the disc is secure.

Do not overtighten. Excess force can damage plastic surfaces or strip the material.

MOUNTING OPTION #2 - THROUGH-BOLT MOUNT

Best for: thin plastic dashboards, interior panels, or any surface that flexes.

HARDWARE USED IN THIS PHASE:

- Thick Disc
- 8-32 x 5/8" flat head machine screw
- Oversized backing washer
- 8-32 serrated flange nut

INSTRUCTIONS

- 1 Place the Thick Mob Disc in the desired location and mark the center hole.
- 2 Drill a hole through the mounting surface sized for the included machine screw.
- 3 Insert the 8-32 machine screw through the center of the disc and through the mounting surface.
- 4 On the back side, place the oversized washer over the machine screw.
- 5 Thread on the serrated flange nut and tighten until secure. Make sure the disc is firmly seated and does not move.