Safety Guidelines: Stop the vehicle in a safe location or have a passenger use the system. Safely operate the vehicle, obey all laws and regulations, and use good judgment at all times. Note: User assumes sole responsibility for and all risk in using this system. General Guidelines: Install the device in a non-obstructive safe location within the vehicle cab. Avoid obstructing the following: Vehicle operation. Visibility through windows. Safe entry or exit, Safety devices such as air bags. Firmly secure the device to stay in place despite vibrations, shocks bumps, or vehicle accidents. Do not use this system or any computer system while operating a motor vehicle. Mob Armor is not responsible or liable for personal and or property damage.

Warning: Improper installation of phone may cause mount failure under shock and vibration. The tighter you clamp the phone in the Mob Mount arms the more securely it will hold the phone.

WARRANTY

For assistance, please contact us directly at:

or Customer Service: (805) 214-1815

-or Video Instructions visit www.mobarmor.com/how-to

What does your 109% Satisfaction Guarantee mean? Our 100% Satisfaction Guarantee means we guarante you will be satisfied with your Mob Armor Product, or we will refund your money. If you are unsatisfied with your product at any time within 30 days of your purchase, you can return it to us for a full refund, no questions asked. You pay shipping back to us. We do not refund any shipping cost.

What warranty does Mob Armor offer?

The Mob Armor Warranty covers all defects in workmanship or materials of our products for up to one year. This warranty applies only to the original purchaser at retail and may not be transferred. This warranty not yocvess defects a shiring under normal usage and does not cover any malfunction, damage or failure due to accident, missue, abuse, neglect, alteration, modification or repairation by other than an authorized service center for Mob Armor products. Stratching of the powder-coated surface, anodizing or plastic constitutes normal wear and is not covered under warranty.

PN-6271





INSTRUCTIONS FOR

MOB MOUNT SWITCH CLAW



INSTRUCTIONS FOR MOB MOUNT SWITCH CLAW

Attach mount to location



Open Clamp

Rotate clamp knob counterclockwise to open mouth of clamp.

2 Close Clamp

Rotate clamp knob clockwise until snug on bar

Clamp Position

Adjust ball pivot knob as desired.

Insert phone into mount

30

Squeeze slide and base firmly around phone when tightening slide knob!

2 Loosen slide knob to free slide.

1) Place phone in Mob Mount.

2) Squeeze the slide and base around phone.

3 Tighten slide knob to secure phone.